

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An apparatusApparatus for 3D shape measurement,
comprising:
 - (A)—a laser projecting device(1-1), said device consists ofincluding a line-laser projector(1-1a) and LEDs(1-1b) attached to the line-laser projector as markers for estimating the position and orientation of the laser projecting device;
 - (B)—an image capturing device(1-2) for capturing the laser projecting device and a target object; and
 - (C)—a computer(1-3) for detecting a projected line-laser light and LEDs from a captured image and processing the image to compute a 3D shape measurement.
2. (Currently Amended) The apparatus for 3D shape measurement defined asin claim 1, being further provided withcomprising a display device(2-4) for displaying the 3D shape captured by the apparatus.
3. (Currently Amended) A method for 3D measurement using the apparatus of claim 1, the method comprising the steps of:
 - (A) projecting a line-laser to an object by using the apparatus defined as claim 1(1-1), the apparatus having LEDs attached to the line-laser projector for estimating the position and orientation of the laser projecting device;
 - (B) capturing the projected line-laser light (1-5) and the LEDs at the same time using on the apparatus defined as claim 1 bythe image capturing device(1-2) at the same time; and

(C) calculating, using the computer, the 3D shape of the object from the captured image using a triangulation method by computer(1-3).

4. (Currently Amended) A method and a system for displaying information, comprising:

(A)-means for processing the steps defined as in claim 3 in real-time; and

(B)-means for displaying the 3D shape acquired by the previously defined steps on a display device(2-5).

5. (Currently Amended) A method for improving 3D shape ~~efusing~~ a triangulation method, the method comprising the steps of:

(A)-selecting 3D points precisely measured by other methods or accurate 3D points with high accuracy from the 3D shape acquired by the method ~~defined as of~~ claim 3 as known 3D points; and

calculating a difference between the 3D depth value of a known 3D point and the 3D depth value estimated by the method of claim 3 as an error function; and

(B)-correcting 3D shapes by using the selected accurate 3D points ~~the position and orientation of the laser projecting device by minimizing the error function.~~